

Overview

D/AVE NX is the latest and most powerful addition to the D/AVE family of rendering cores. It is the first IP to bring full OpenGL ES 2.0 rendering (with some ES 3.0 / 3.1 extensions) to the FPGA and SoC world and is prepared to support OpenGL SC (Safety Critical). Targeted for graphics applications on displays up to 4K x 4K resolution in the Industrial, Medical, Military, Avionics, Automotive and Consumer markets, **D/AVE NX** is designed to meet the sweet spot of performance and footprint.



By enabling the use of programmable shaders even on small devices, high quality 2D and full 3D applications can be realized using the **D/AVE NX** core. Support for industry standard APIs like OpenGL ES 2.0 allows for rapid development of high-end user interfaces by leveraging third party frameworks like Qt, SCADE or Android, and makes new, future proof implementations possible.


D/AVE NX can scale easily to fit exactly into the resource / performance sweet spot for a particular application. Entire device families can be equipped with differently scaled variants of the core, making all of them fully software compatible. A single unified software stack and the guarantee to produce exactly the same visual result (at different speeds) allows saving significant development resources.

D/AVE NX is highly efficient as the internal multi-level scheduler can maximize the utilization of every HW element even better than the fixed function pipeline of the successful **D/AVE** cores could. Scheduling also does not have to be precomputed in the compiler, simplifying the compiler and driver architecture considerably.

Technology Details

System Features

- Scalability throughout the entire design
 - Scaling from tiny footprint up to high end performance
 - Scalable unified shader architectures are a perfect fit for FPGAs
 - Exact same driver / software stack can be used on all versions
 - Enables the same output at different speeds
- Unified Shader Architecture
 - Dynamic, fully reconfigurable shaders
 - Efficient support for branches / divergent control flow
 - Fully IEEE compatible floating point ALUs (incl. rounding, denormals etc.)
 - Non-constant varying indexing
 - True integer arithmetic (8bit, 16bit, 32bit)
 - Multi-level caches for shader memory
- Massively parallel execution with fine grained Multithreading



- Thread context switch near instantaneous (~2 cycles)
- Advanced task scheduler supporting both long- and short-term stalls
- Architecture is able to eliminate hundreds of cycles of latency
- Concurrent use from multiple applications
- Job preemption possible on fragment level
- Bandwidth reduction techniques
 - On the fly data compression/decompression
 - Sophisticated caching mechanisms
- Application optimization and debugging support
 - Multiple hardware performance counters
 - Detailed analysis of shader stalls and scheduling
- Pipelined architecture for high clock frequencies
- System security features
 - Stop on bus error for integration with memory protection units
 - Hardware out-of-framebuffer memory access protection

Rendering

- Full support of all OpenGL ES 2.0 rendering features (with some OpenGL ES 3.0 / 3.1 extensions)
- High render quality
 - Highly accurate sub pixel positioning, interpolation, and filtering
 - Multiple anti-aliasing techniques (including MSAA)
- Effective texture compression
 - Multiple high quality standard codecs ETC2/EAC, ASTC
 - Maximizing the visual quality with a given bandwidth
 - Saving storage and transfer resources
- Hardware supported blending
 - Normal alpha blending
 - Linear color-space blending
- Various texture and framebuffer formats
 - 8 bit alpha/luminance, ARGB4444, ARGB1555, RGB565, ARGB8888 etc.
 - Floating point texture support
 - 3d texture and texture array support
- High resolutions
 - Frame buffers and textures up to 4k x 4k pixels
- Support for Image Transformation & Warping
- Composition Engine

Power Management

- Memory blocks controlled by Chip Select port
- Prepared for efficient automatic clock gating
- Global clock gating as option

Integration

- Single clock domain architecture
 - Bus interface clock frequency may differ from core frequency

- High latency capable
- Optional internal arbitration to work with a single bus master
- Adaptors for common bus protocols
 - ARM AMBA: APB for register access, AXI for memory bus master access
 - Intel PSG Avalon as bus adaptors for both register and bus master access
 - Other bus protocols can be easily adapted

Resource Usage

The actual resource usage of D/AVE NX depends mainly on the number of Shader Units (SUs), the number of Arithmetic Logic Units (ALUs) per shader unit and partly on the bus and cache configuration.

Verification Concept

A 100% algorithmic equivalent C model is used as reference for the verification of the RTL code. This real-time capable reference model is called 'Soft D/AVE' which acts as a pixel accurate emulator on Windows PC. The emulator is also used for driver and application development.

The following test metrics are used:

- Functional Coverage
- Code Coverage using Cadence IUS
- Static Code Analysis
- Timing Checks
- FPGA prototyping


Software

Drivers

TES provides Khronos conformant OpenGL ES 2.0 and EGL drivers. Both drivers rely on a low-level D/AVE NX driver layer, abstracting hardware details like the register access and making porting to different CPUs / Operating systems a lot easier.

All drivers have the following features:


- Fully reentrant & thread-safe
- Minimal OS dependency (HAL part separated)
- No inline assembler required
- Support for multiple D/AVE NX instances
- Multi-threading support, i.e. multiple applications can use D/AVE NX concurrently
- Small memory footprint



D/AVE NX reference Qt system solution on Yocto-Linux

TES delivers a complete reference system solution for Intel PSG SoCs supporting selected reference boards (e.g. D10-Nano SoC board featuring Cyclone 5 SoC) including:

- Qt 5.x
- Yocto Linux OS
- OpenGL ES 2.0 and EGL drivers for D/AVE NX and CDC-200NX as source code
- Qt and native OpenGL ES 2.0 example applications as source code
- Build scripts to check out required repositories (Yocto-Linux, Qt, meta layers, drivers, ...) and build the D/AVE NX demo SD card image as well as the complete SDK.
- D/AVE NX as Megacore IP block (QSys component)
- CDC-200NX Display Controller as Megacore IP block (QSys component)



The delivered package includes everything to evaluate the IP and start an own integration and application project.

Sales & Marketing Contact

TES Electronic Solutions GmbH
Wandalenweg 20
20097 Hamburg
Germany
<mailto:graphics@tes-dst.com>
www.tes-dst.com